

TECHNICAL DATA SHEET

Wire cable spray

Art. no. 0893 105 8

P. Qty.: 1 / 12

Protective wax with OMC₂ for lubricating and preserving

- Sprayable corrosion protection wax
- Anti-wear additives
- Does not drip with heat development
- Optimal creeping capacity
- Outstanding resistance to water
- Contains additives with OMC 2 technology
- Free from solid lubricants
- Seal compatibility with Viton and Perbunan elastomers
- Weather-resistant



Chemical basis	Synthetic wax oxidant
Colour	Brown
Smell/fragrance	Characteristic
Density	0.775 g/cm ³
Density conditions	at 20 °C
Min. temperature conditions	-40 °C
Max. temperature conditions	120 °C
Corrosion protection period/category	No rust spots after 7 cycles
Corrosion protection period conditions	in accordance with DIN 51802
Behaviour in the presence of water	0-90
Conditions for behaviour in the presence of water	in accordance with DIN 51807-1
Resin-free	Yes
Silicone-free	Yes
Acid-free	Yes
AOX-free	Yes
Contents	500 ml
Shelf life from production	24 Month

Application area

High-quality protective wax with OMC 2 technology, for lubrication and preservation

Application information

For universal use. Lubricates and preserves wire ropes on winches, lifts, conveying and lifting systems and support and attaching cables.

TECHNICAL DATA SHEET

Thoroughly pre-clean parts using brake cleaner and spray evenly.
Repeated application provides a thick protective film.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.